

भारतीय अन्तर्देशीय जलमार्ग प्राधिकरण

(पोत परिवहन मंत्रालय, भारत सरकार) INLAND WATERWAYS AUTHORITY OF INDIA

(Ministry of Shipping, Govt. of India)

क्षेत्रीय कार्यालय : पि-७८, गार्डेनरीच रोड, कोलकाता-७०० ०४३ (प० बं०) REGIONAL OFFICE : P-78, Garden Reach, Kolkata - 700 043 (W.B.)

GRAM : JALMARG दूरभाष : 2439 0393 / 5577 / 6055 फेक्स : 2439 5570 / 1740

Email: iwaical@yahoo.com

IWAI/KOL/8/TERMINAL/2022-23

Date:-17.09.2022

NOTICE FOR INVITING QUOTATION

Sealed quotations are invited from reputed and experienced contractors for the work of "Construction of temporary structure for store room of size (6m \times 3m) at RO IWAI, Kolkata premises RO IWAI, Kolkata building" as per the annexure enclosed herewith on the following terms and conditions.

TERMS & CONDITIONS

- 1. The price may be quoted including all the costs such as labour, taxes, materials, transportation etc except GST.
- 2. The work shall be completed at, IWAI, Kolkata Premises within 10(Ten) days from the date of receipt of the work order.
- 3. 90% payment shall be released by RTGS within 15 days from the date of submission of bill and duly certification of the bill by the officer concerned after deduction of the statutory dues if any. Balance 10% shall be released after 6 month on satisfactory completion of the guaranty period and the same shall be duly certified by officer concerned. Further, GST as applicable shall be reimbursed, only after submission of proof of its remittance from concerned department.
- 4. In case of delay in completion of works, liquidated damage ω 1.5% per two days subject to a maximum of 5% will be charged.
- 5. The firm should also require submitting self certified copy of PAN Card, Registration certificate, GST, and credential certificate etc.

The sealed quotations should be reach to IWAI, Kolkata office latest by on or before 21.09.2022 at 1300 hrs. The sealed bids will be opened on same at 1330 hrs.

(Arvind Kumar)

DIRECTOR(I/C)

Head Office: A-13, Sector-I, NOIDA, U.P. Pin - 201301

Phone: 0120-2543972 / 4004 / 2521764, Fax: 0120-02543973 / 4009 / 4041 / 2521664

E-mail: iwainoi@hub.nic.in Website: www.iwai.nic.in

1 may we ear 2 :1 gr in 3 de 4 de 5 P. far	arth work in excavation by mechanical means (Hydraulic excavator)/ nanual means over areas (exceeding 30 cm in depth, 1.5 m in width as rell as 10 sqm on plan) including getting out and disposal of excavated arth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-incharge roviding and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:3:6 (1 cement : 3 coarse sand (zone-III) derived from natural sources : 6 raded stone aggregate 20 mm nominal size derived from natural sources) in foundation trenches all complete as per specification & direction of EIC. Brick work with common burnt clay F.P.S. (non modular) bricks of class lesignation 7.5 in foundation and plinth in:Cement mortar 1:4 (1 cement : coarse sand) all complete as per specification and direction of EIC Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in Cement mortar 1:4 (1 cement : 4 coarse sand) all complete as per specification and direction of EIC Providing 12 mm thick cement plaster in cm1:6 (1 cement: 6 fine sand) in	cum	0.60 2.55	
2 ex :1 gr im 3 d4 d4 d5 d4 d6	excluding the cost of centering and shuttering - All work up to plinth level 1:3:6 (1 cement : 3 coarse sand (zone-III) derived from natural sources : 6 raded stone aggregate 20 mm nominal size derived from natural sources) in foundation trenches all complete as per specification & direction of EIC. Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:Cement mortar 1:4 (1 cement : 4 coarse sand) all complete as per specification and direction of EIC. Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in Cement mortar 1:4 (1 cement : 4 coarse sand) all complete as per specification and direction of EIC. Providing 12 mm thick cement plaster in cm1:6 (1 cement: 6 fine sand) in	cum	2.55	
3 de 4 B de 5 cc 5 Pr fa 6 Pu	lesignation 7.5 in foundation and plinth in:Cement mortar 1:4 (1 cement : coarse sand) all complete as per specification and direction of EIC Brick work with common burnt clay F.P.S. (non modular) bricks of class lesignation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in Cement mortar 1:4 (1 cement : 4 coarse sand) all complete as per specification and direction of EIC Providing 12 mm thick cement plaster in cm1:6 (1 cement: 6 fine sand) in			
4 do sl co	designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in Cement mortar 1:4 (1 cement : 4 coarse sand) all complete as per specification and direction of EIC Providing 12 mm thick cement plaster in cm1:6 (1 cement: 6 fine sand) in	cum	6.51	
6 Pu	Providing 12 mm thick cement plaster in cm1:6 (1 cement: 6 fine sand) in			
u S	aced wall all complete as per specification and direction of EIC	sqm	99.62	
h	Providing 15 mm thick cement plaster in cm1:6 (1 cement: 6 fine sand) in unfaced wall all complete as per specification and direction of EIC	sqm	38.84	
, c	Supplying, fabricating, fitting & fixing 80mm x 40mm tubular rectangular nollow tubes Electric resistance or induction butt welded tubes for Steel work in built up, with a wall thickness 1.5mm in frame of roof including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. all complete as per specification and direction of EIC.	kg	193.84	
8 d a	Providing and fixing 1mm thick M.S. sheet door & Windows with frame of 40x40x6 mm angle iron and 3 mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, Using M.S. angels 40x40x6 mm for diagonal braces including applying a priming coat of approved steel primer all complete upto plinth level all complete as per specification and direction of EIC.	sqm	3.62	
9 0	Supplying, fabricating, fitting & fixing coloured coated Roof and Wall sheets of 0.6mm thick & 1220mm width manufactured from zinc/ aluminum alloy coated high tensile steel along with J, L-hooks, bitumen washer, nut/bolts of required size all complete as per specification & direction of EIC	l som	23.75	
10	Providing and laying damp-proof course 50mm thick with cement concrete 1:2:4 (1 cement: 2 coarse sand (zone-III) derived from natural sources: 4 graded stone aggregate 20mm nominal size derived from natural sources) all complete as per specification and direction of EIC.	sam	8.63	