

# भारतीय अन्तर्देशीय जलमार्ग प्राधिकरण

(पत्तन, पोत परिवहन और जलमार्ग मंत्रालय, भारत सरकार)

### **INLAND WATERWAYS AUTHORITY OF INDIA**

(Ministry of Ports, Shipping and Waterways, Govt. of India) क्षेत्रीय कार्यालय : पी-७८, गार्डेनरीच रोड, कोलकाता - ७०० ०४३ (प० बं०)

REGIONAL OFFICE: P-78, Garden Reach Road, Kolkata - 700 043 (W.B.)

दुरभाष : 2439 0393 / 5577 / 6055, फैक्स : 2439 5570



E-mail: iwaical@yahoo.com dirkol.iwai@nic.in

#### IWAI/KOL/MM/78/2020-21

Date: - 21.02.2022

## **NOTICE FOR INVITING QUOTATION**

Sealed quotations are invited from reputed and experienced contractors for the work of "Repair & Renovation of Ground floor at RO IWAI, Kolkata premises" as per the annexure enclosed herewith on the following terms and conditions.

#### **TERMS & CONDITIONS**

- 1. The price may be quoted including all the costs such as labour, taxes, materials, transportation etc except GST.
- 2. The work shall be completed at, IWAI, Kolkata within 5(Five) days from the date of receipt of the work order.
- 3. 90% payment shall be released by RTGS within 15 days from the date of submission of bill and duly certification of the bill by the officer concerned after deduction of the statutory dues if any. Balance 10% shall be released after 6 month on duly certified by officer concerned on satisfactory completion of the guaranty period. Further, GST as applicable shall be reimbursed, only after submission of proof of its remittance from concerned department.
- 4. In case of delay in completion of works, liquidated damage @1.5% per two days subject to a maximum of 5% will be charged.
- 5. The firm should also require submitting self certified copy of PAN Card, Registration certificate, GST, and credential certificate etc.

The sealed quotations should be reach to IWAI, Kolkata office latest by on or before 02.03.2022 at 1100 hrs. The sealed bids will be opened on same at 1130 hrs.

-sd-

DIRECTOR

Head Office : A-13, Sector-I, NOIDA, U.P. Pin - 201 301
Phone : 0120-2543972 / 4004 / 2521764, Fax : 0120-02543973 / 4009 / 4041 / 2521664
E-mail : iwalnoi@hub.nic.in Website : www.iwai.nic.in / www.iwai.gov.in

| Bill of quantity for Repair & Renovation of Ground floor at RO IWAI, Kolkata premises |  |       |          |               |                 |  |  |
|---|--|-------|----------|---------------|-----------------|--|--|
| S1. No.   | Description of item  | Unit  | Quantity | Rate (In Rs.) | Amount (In Rs.) |  |  |
| 1   | Dismantling tile work in floors and skirtings For thickness of tiles 10 mm to 25 mm laid in cement mortar including stacking material within 50 metres lead all complete as per specification & direction of EIC.  | sqm   | 40.64    |               |                 |  |  |
| 2   | Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead   | sqm   | 15.00    |               |                 |  |  |
| 3   | Dismantling of flushing cistern of all types (C.I./PVC/Vitrious China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead. (1 nos cistern ) all complete as per specification & direction of EIC.  | nos   | 1.00     |               |                 |  |  |
| 4   | Dismantling steel work manually/ by mechanical means in<br>built up sections without dismembering and stacking within<br>50 metres lead as per direction of Engineer-in-charge   | kg    | 4.00     |               |                 |  |  |
| 5   | Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead Of area 3 sq. metres and below   | nos   | 6.00     |               |                 |  |  |
| 6   | Dismantling G.I. pipes (external work) including excavation and refilling trenches after taking out the pipes, manually/by mechanical means including stacking of pipes within 50 metres lead as per direction of Engineer-in-charge:  | meter | 7.80     |               |                 |  |  |
| 7   | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete  | sqm   | 53.25    |               |                 |  |  |
| 8   | Providing and laying rectified Glazed Ceramic floor/skirting tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS: 15622, of approved make, in all colours, shades, except White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement Mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including pointing the joints with white cement and matching pigments etc., all complete as per specification and direction of EIC | sqm   | 55.64    |               |                 |  |  |
| 9   | Providing 12mm thick cement plaster in 1:4 (1 cement: 4 fine sand) all complete as per specification and direction of EIC (Quantity vide item no. 2)   | sqm   | 15.00    | 1 10000       |                 |  |  |
| 10  | Distempering with 1st quality acrylic distemper (ready made) having VOC content less than 50 gm per ltr. of approved manufacturer and of required shade and colour complete. as per manufacturer's specification all complete as per specification and direction of EIC(Quantity vide item no.7 multiplied with multiplying factor 1.5)  | sqm   | 118.85   |               |                 |  |  |

- - - · ·

| 11 | Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete as per specification & direction of EIC.  | kg  | 30.00 |  |
|----|--|-----|-------|--|
| 12 | Supplying, fitting and fixing Float glass panes of nominal thickness 5 mm with putty & other chemicals in window frame all complete as per specification and direction of EIC (Add 10% wastage)  | sqm | 2.18  |  |
| 13 | Providing and fixing ISI marked flush door shutters 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws conforming to IS: 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters all complete as per specification and direction of EIC   | sqm | 2.10  |  |
| 14 | Supplying, fitting and fixing wire mesh for mosquito protection all complete as per specification and direction of EIC. (Add 15% extra for wastage.)   | sqm | 1.98  |  |
| 15 | Providing and fixing white vitreous china pedestal type water closet (European type) with seat and lid, 10 litre low level white vitreous china flushing cistern & C.P. flush bend with fittings & C.I. brackets, 40 mm flush bend, overflow arrangement with specials of standard make and mosquito proof coupling of approved municipal design complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required :W.C. pan with ISI marked white solid plastic seat and lid all complete as per specification and direction of EIC | nos | 1.00  |  |
| 16 | Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm and 340x410x265 mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions and G.I clamps complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required Range of three rinal basins all complete as per specification and direction of EIC  | set | 1.00  |  |
| 17 | Providing and fixing wash basin with C.I. brackets, 15 mm dia CP Brass single hole basin mixer of approved quality and make, including painting of fittings and brackets, cutting and making good the walls wherever required:- (a) White Vitreous China Wash basin size 550x400 mm with a 15 mm CP Brass single hole basin mixer all complete as per specification and direction of EIC.  | nos | 1.00  |  |
| 18 | Providing and fixing hand shower, 15 mm nominal bore, weighing not less than 40 gms including all its fitting all complete as per specification and direction of EIC   | nos | 1.00  |  |
| 19 | Providing and fixing 15mm ss tap of approved quality by EIC all complete as per specification and direction of EIC   | nos | 2.00  |  |

| 20 | Providing and fixing 25mm PVC water supply pipe alongwith all its GI/PVC fittings all complete as per specification and direction of EIC                       | r-m           | 20.00 |           |             |
|----|--|---------------|-------|-----------|-------------|
| 21 | S/F/F ss bathing shower all complete with all its fitting as per specification & direction of EIC  | nos           | 1.00  |           |             |
| 22 | S/F/F PVC S & P trap of 100 to 200mm dia alongwith PVC pipe of 100 to 200mm dia for waste water outlet all complete as per specification nad direction of EIC. | r-m           | 10.00 |           |             |
|    | Supplying of electrical item mentioned below wiring all complete as per specification and direction of EIC   |               |       |           |             |
|    | 4mm Copper wire  | r-m           | 22.00 |           |             |
|    | 6mm copper wire  | r-m           | 10.00 |           |             |
| 23 | PVC pipe for wiring  | r-m           | 30.00 |           |             |
|    | Modular 5A switch  | nos           | 8.00  |           |             |
|    | 16A five pin socket  | nos           | 2.00  |           |             |
|    | 12 Module (200mmX150mm)  | nos           | 2.00  |           |             |
|    | Modular base & cover plate on existing modular metal boxes 12 Module (200mmX150mm)   | nos           | 2.00  |           |             |
|    | Metal box  | nos           | 2.00  |           | No serios e |
|    | LED bulb 18W   | nos           | 4.00  |           |             |
|    | Exaust fan 14"   | nos           | 2.00  |           |             |
|    | Bulb holder  | nos           | 4.00  |           |             |
|    | Celing rose  | nos           | 4.00  |           |             |
|    |  | ATTEN HOORING |       | Sub total |             |